

MULTIPLE OUTPUT LINEAR D.C. POWER SUPPLY



GPS-2303/3303/4303



Patent No: ZL 02 3 35264 . 7

FEATURES

- * 2, 3 and 4 Independent Isolated Output
- * Four "3 Digits" LED Displays
- * 0.01% Load and Line Regulation
- * Low Ripple and Noise
- * Tracking Operation and Auto Series/Parallel Operation
- * Output ON/OFF Switch
- * Output Voltage and Current Setting When Output Disable (Except for GPS-2303)
- * Fan Speed Control Circuit to Minimize Fan Noise
- * Over Load and Reverse Polarity Protection
- * Optional European Jack Type Terminal

GPS-001

Voltage/Current protection Knob



Rear Panel



GPS-3303

The GPS-Series are 2-4 channel, 180 to 200W output, linear DC power supplies. Overload and reverse polarity protection and an output on/off switch keep the GPS-Series and their load safe from unexpected conditions. A High regulation (0.01%+3mV) and low ripple/noise (< 1mVrms, 5Hz~1MHz) are maintained for channel 1 and 2 in constant voltage mode. Automated cooling fan speed control minimizes fan noise according to load conditions, ensuring quiet operation. The GPS-Series are an ideal solution for lightweight, inexpensive bench-top or portable applications requiring high regulation and multiple outputs.

SPECIFICATIONS										
		GPS-4303				GPS-3303			GPS-2303	
OUTPUT MODE										
	CH1	CH2	CH3	CH4	CH1	CH2	CH3	CH1	CH2	
Voltage	0 ~ 30V		2.2 ~ 5.2V	8 ~ 15V	0 ~ 30V		5V Fixed	0 ~ 30V		
Current	0 ~ 3A		1A Max.	1A Max.	0 ~ 3A		3A Max.	0 ~ 3A		
Tracking Series Voltage	0 ~ 60V		----		0 ~ 60V		----		0 ~ 60V	
Tracking Parallel Current	0 ~ 6A		----		0 ~ 6A		----		0 ~ 6A	
CONSTANT VOLTAGE OPERATION (CH1, CH2)										
Line Regulation	≤ 0.01% + 3mV									
Load Regulation	≤ 0.01% + 3mV (rating current ≤ 3A) ≤ 0.02% + 5mV (rating current > 3A)									
Ripple & Noise	≤ 1mVrms, 5Hz ~ 1MHz									
Recovery Time	≤ 100μS (50% Load change, Minimum load 0.5A)									
CONSTANT CURRENT OPERATION (CH1, CH2)										
Line Regulation	≤ 0.2% + 3mA									
Load Regulation	≤ 0.2% + 3mA									
Ripple & Noise	≤ 3mArms									
TRACKING OPERATION (CH1, CH2)										
Tracking Error	≤ 0.5% + 10mV of CH1									
Series Regulation	≤ 0.01% + 5mV									
Load Regulation	≤ 300mV									
Ripple & Noise	≤ 2mVrms, 5Hz ~ 1MHz									
CH3 OPERATION (for GPS-3303/4303)										
CH3 Voltage	GPS-4303 : 2.2V ~ 5.2V, GPS-3303 : 5V Fix									
Line Regulation	≤ 5mV									
Load Regulation	≤ 15mV									
Ripple & Noise	≤ 2mVrms, 5Hz ~ 1MHz									
Current Output	GPS-4303 : 1A, GPS-3303 : 3A									
CH4 OPERATION (for GPS-4303)										
CH4 VOLTAGE	8V ~ 15V									
Line Regulation	≤ 5mV									
Load Regulation	≤ 10mV									
Ripple & Noise	≤ 2mVrms, 5Hz ~ 1MHz									
Current Output	1A									
METER										
Digital	3 digits 0.5" LED display GPS-4303/3303 Out ON Accuracy ± (0.5% of rdg + 2 digits) GPS-4303/3303 Out OFF Accuracy ± (0.5% of rdg + 8 digits) GPS-2303 Accuracy ± (0.5% of rdg + 2 digits)									
INSULATION										
Chassis and Terminal	≥ DC 500V / 20MΩ									
Chassis and AC Cord	≥ DC 500V / 30MΩ									
POWER SOURCE										
AC 100V/120V/220V±10%, 230V(+10%~-6%), 50/60Hz										
DIMENSIONS & WEIGHT										
255(W) x 145(H) x 265(D) mm, Approx. 7 kg										

ORDERING INFORMATION

- GPS-4303** 4-channels, 200W D.C. Power Supply
- GPS-3303** 3-channels, 195W D.C. Power Supply
- GPS-2303** 2-channels, 180W D.C. Power Supply

ACCESSORIES :

User manual x 1, Power cord x 1,
GPS-4303: Test lead GTL-104 x 2, GTL-105 x 2 ; European test lead GTL-203 x 2, GTL-204 x 2, GTL-201A x 1
GPS-3303: Test lead GTL-104 x 2, GTL-105 x 1 ; European test lead GTL-203 x 1, GTL-204 x 2, GTL-201A x 1
GPS-2303: Test lead GTL-104 x 2 ; European test lead GTL-204 x 2, GTL-201A x 1

OPTIONAL ACCESSORIES

GPS-001 Voltage/Current Protection Knob (It's available OCT/07' production batch)

Available from



CALTEST
Instruments Ltd
Specialists in power
and instrumentation

Power sources and test instrumentation solutions

Caltest have been providing power sources and test instrumentation solutions for over 20 years and are proud to represent a number of industry leading manufacturers.

As well as supplying world class power sources and test instrumentation Caltest also has a service centre and UKAS calibration laboratory.

NEED HELP?

CALL US:

01483 302 700

or visit our website for more details

Caltest Instruments Ltd
4 Riverside Business Centre
Walnut Tree Close
Guildford
Surrey GU1 4UG
United Kingdom

Tel: +44 (0) 1483 302 700

Fax: +44 (0) 1483 300 562

sales@caltest.co.uk

www.caltest.co.uk

Sales • Rentals • Service • UKAS Calibration

